

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App:+86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-002 ENC Mono Solution1	Headset Model: UC-002 ENC Mono Solution2
Audio	Microphone Type	2μm ECM array (1 omnidirectional, 1 unidirectional)	2μm ECM array (2 omnidirectional)
	Microphone Frequency Range	100Hz – 8kHz	50Hz – 8kHz
	Microphone Sensitivity	-38±3dB	-38±2dB
	Speaker Size	30mm	30mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	92±3dB	95±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC Microphone	YES	YES
	ANC	NO	NO
	Passive Noise Cancellation	YES	YES
Ease of Use	Call Control	Answer/End Call Microphone mute (button) volume adjustment	Answer/End Call Microphone mute (button) volume adjustment
	Microphone Boom Rotation	180°	180°
	Busylight	Integrated headlights	Integrated headlights
	Ringtone	/	/
	Compatibility	Subject to actual product testing	Subject to actual product testing
Connectivity	Connection	USB 2.0, USB-A, USB-C, or USB-A & C, plug and play.	USB 2.0, USB-A, USB-C, or USB-A & C, plug and play.
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions(L×W×H)	205x180X40mm	205x180X40mm
	USB Cable Length	Control cable: 120 cm; Headset cable: 60 cm	Control cable: 120 cm; Headset cable: 60 cm
	Warranty	1 Year	1 Year
	Weight	Bare device: 104.5g, including USB cable; Packaging included: 200.5g (including cardboard box, cardboard tray, and instruction manual)	Bare device: 104.5g, including USB cable; Packaging included: 200.5g (including cardboard box, cardboard tray, and instruction manual)
	Certifications	CE,FCC,ROHS	CE,FCC,ROHS
	Operating Temperature	-10°C to +50°C	-10°C to +50°C

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App:+86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-003 ENC Mono Solution 1	Headset Model: UC-003 ENC Mono Solution 2
Audio	Microphone Type	2μm ECM array (1 omnidirectional, 1 unidirectional)	2μm ECM array (2 omnidirectional)
	Microphone Frequency Range	100Hz – 8kHz	50Hz – 8kHz
	Microphone Sensitivity	-38±3dB	-38±2dB
	Speaker Size	40mm	40mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	106±3dB	107±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC Microphone	YES	YES
	ANC	NO	NO
	Passive Noise Cancellation	YES	YES
Ease of Use	Call Control	Answer/End Call Microphone mute (button or boom lifting device) volume adjustment	Answer/End Call Microphone mute (button or boom lifting device) volume adjustment
	Microphone Boom Rotation	270°	270°
	Busylight	optional	optional
	Ringtone	The USB adapter with a built-in speaker can emit an audible alarm sound.	The USB adapter with a built-in speaker can emit an audible alarm sound.
	Compatibility	Subject to actual product testing	Subject to actual product testing
Connectivity	Connection	USB 2.0, USB-A, USB-C, or USBA & C, plug and play.	USB 2.0, USB-A, USB-C, or USBA & C, plug and play.
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions(L×W×H)	210x192X55mm	210x192X55mm
	USB Cable Length	Control cable: 120 cm; Headset cable: 60 cm	Control cable: 120 cm; Headset cable: 60 cm
	Warranty	1 Year	1 Year
	Weight	Bare device: 157g, including USB cable; Packaging included: 292.5g (including cardboard box, cardboard tray, and instruction manual)	Bare device: 157g, including USB cable; Packaging included: 292.5g (including cardboard box, cardboard tray, and instruction manual)
	Certifications	CE,FCC,ROHS	CE,FCC,ROHS
	Operating Temperature	Temperature range: -10°C to +50°C	Temperature range: -10°C to +50°C

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App:+86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-006 ENC Mono Solution1	Headset Model: UC-006 ENC Mono Solution2
Audio	Microphone Type	2μm ECM array (1 omnidirectional, 1 unidirectional)	2μm ECM array (2 omnidirectional)
	Microphone Frequency Range	100Hz – 8kHz	50Hz – 8kHz
	Microphone Sensitivity	-38±3dB	-38±2dB
	Speaker Size	40mm	40mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	107±3dB	106±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC Microphone	YES	YES
	ANC	NO	NO
	Passive Noise Cancellation	YES	YES
Ease of Use	Call Control	Answer/End Call Microphone mute (button or boom lifting device) volume adjustment	Answer/End Call Microphone mute (button or boom lifting device) volume adjustment
	Microphone Boom Rotation Angle	270°	270°
	Busylight	optional	optional
	Ringtone	/	/
	Compatibility	Subject to actual product testing	Subject to actual product testing
Connectivity	Connection	USB 2.0, USB-A, USB-C, or USB-A & C, plug and play.	USB 2.0, USB-A, USB-C, or USB-A & C, plug and play.
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions(L×W×H)	210x192X55mm	210x192X55mm
	USB Cable Length	Control cable: 120 cm; Headset cable: 60 cm	Control cable: 120 cm; Headset cable: 60 cm
	Warranty	1 Year	1 Year
	Weight	Bare device: 143.5g, including USB cable; Packaging included: 277g (including cardboard box, cardboard tray, and instruction manual)	Bare device: 143.5g, including USB cable; Packaging included: 277g (including cardboard box, cardboard tray, and instruction manual)
	Certifications	CE,FCC,ROHS	CE,FCC,ROHS
	Operating Temperature	-10°C to +50°C	-10°C to +50°C