

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App:+86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-002QD Mono Solution1	Headset Model: UC-002 QD Mono Solution2
Audio	Microphone Type	1μm ECM array (1 omnidirectional)	1μm ECM array (1 unidirectional)
	Microphone Frequency Range	70Hz – 10kHz	50Hz – 8kHz
	Microphone Sensitivity	-38±3dB	-38±2dB
	Speaker Size	30mm	30mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	92±3dB	95±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC Microphone	Microphone with noise reduction	/
	ANC	No	No
	Passive Noise Cancellation	Yes	Yes
Ease of Use	Call Control	Answer/End Call	Answer/End Call
		Mute (button), Volume Up/Down	Mute (button), Volume Up/Down
	Microphone Boom Rotation Angle	180°	180°
	Busylight	No	No
	Ringtone	/	/
Connectivity	Compatibility	Subject to actual product testing	Subject to actual product testing
	Connection	USB、RJ9、3.5mm、Type-C(Optional)	USB、RJ9、3.5mm、Type-C(Optional)
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions (L×W×H)	175X218X109mm	175X218X109mm
	Warranty	1 Year	1 Year
	Weight	116.9g	116.9g
	Certifications	CE , FCC	CE , FCC
	Operating Temperature	-10°C to +50°C	-10°C to +50°C

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App:+86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-003 QD Mono Solution1	Headset Model: UC-003 QD Mono Solution: Bluetrum solution
Audio	Microphone Type	1μm ECM array (1 omnidirectional)	1μm ECM array (1 unidirectional)
	Microphone Frequency Range	70Hz – 10kHz	50Hz – 8kHz
	Microphone Sensitivity	-38±3dB	-38±2dB
	Speaker Size	40mm	40mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	100±3dB	107±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC Microphone	Yes	/
	ANC	No	No
	Passive Noise Cancellation	Yes	Yes
Ease of Use	Call Control	Answer/End Call	Answer/End Call
		Mute (button), Volume Up/Down	Mute (button), Volume Up/Down
	Microphone Boom Rotation	270°	270°
	Busylight	No	No
	Ringtone	/	/
	Compatibility	Subject to actual product testing	Subject to actual product testing
Connectivity	Connection	USB、RJ9、3.5mm、Type-C(Optional)	USB、RJ9、3.5mm、Type-C(Optional)
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions (L×W×H)	175X218X109mm	175X218X109mm
	Warranty	1 Year	1 Year
	Weight	197.5g	197.5g
	Certifications	CE , FCC	CE , FCC
	Operating Temperature	-10°C to +50°C	-10°C to +50°C

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App:+86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-006 QD Mono Solution1	Headset Model: UC-006 QD Mono Solution2
Audio	Microphone Type	1μm ECM array (1 omnidirectional)	1μm ECM array (1 unidirectional)
	Microphone Frequency Range	70Hz – 10kHz	50Hz – 8kHz
	Microphone Sensitivity	-38±3dB	-38±2dB
	Speaker Size	40mm	40mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	100±3dB	105±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC Microphone	Yes	/
	ANC	Yes	/
	Passive Noise Cancellation	No	No
Ease of Use	Call Control	Yes	Yes
		Answer/End Call	Answer/End Call
	Microphone Boom Rotation Angle	Mute (button), Volume Up/Down	Mute (button), Volume Up/Down
	Busylight	270°	270°
	Ringtone	/	/
	Compatibility	Subject to actual product testing	Subject to actual product testing
Connectivity	Connection	USB、RJ9、3.5mm、Type-C(Optional)	USB、RJ9、3.5mm、Type-C(Optional)
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions (L×W×H)	175X218X109mm	175X218X109mm
	Warranty	1 Year	1 Year
	Weight	181.8g	181.8g
	Certifications	CE , FCC	CE , FCC
	Operating Temperature	-10°C to +50°C	-10°C to +50°C