

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App: +86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-002 USB Mono (Single-ear) Solution1	Headset Model: UC-002 Mono (Single-ear) USB Solution2
Audio	Microphone Type	1μm ECM array (1 omnidirectional)	1μm ECM array (1 unidirectional)
	Microphone Frequency Range	70Hz – 10kHz	70Hz – 10kHz
	Microphone Sensitivity	-38±3dB	-38±3dB
	Speaker Size	30mm	30mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	92±3dB	95±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC	Yes	/
	ANC	No	No
	Passive Noise Cancellation	Yes	No
Ease of Use	Call Control	Answer/End Call	Answer/End Call
		Microphone Mute (button), Volume Up/Down	Microphone Mute (button), Volume Up/Down
	Microphone Boom Rotation Angle	180°	180°
	Busylight	No	No
	Ringtone	/	/
	Compatibility	Subject to actual product testing	Subject to actual product testing
Connectivity	Connection	USB 2.0, USB-A, USB-C or USB-A & C, plug and play	USB 2.0, USB-A, USB-C or USB-A & C, plug and play
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions (L×W×H)	175X218X109mm	175X218X109mm
	USB Cable Length	Control cable: 130 cm; Headset cable: 50 cm	Control cable: 130 cm; Headset cable: 50 cm
	Warranty	1 Year	1 Year
	Weight	104.9g	104.9g
	Certifications	CE , FCC	CE , FCC
	Operating Temperature	' -10°C +50°C	' -10°C +50°C

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App: +86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-003 USBMono (Single-ear) Solution1	Headset Model: UC-003 Mono (Single-ear) Solution2
Audio	Microphone Type	1µm ECM array (1 omnidirectional)	1µm ECM array (1 unidirectional)
	Microphone Frequency Range	70Hz – 10kHz	70Hz – 8kHz
	Microphone Sensitivity	-40±3dB	-38±3dB
	Speaker Size	40mm	40mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	97±3dB	106±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC	Yes	/
	ANC	No	No
	Passive Noise Cancellation	Yes	No
Ease of Use	Call Control	Answer/End Call	Answer/End Call
		Microphone Mute (button), Volume Up/Down	Microphone Mute (button), Volume Up/Down
	Microphone Boom Rotation Angle	270°	270°
	Busylight	No	No
	Ringtone	/	/
	Compatibility	Subject to actual product testing	Subject to actual product testing
Connectivity	Connection	USB 2.0, USB-A, USB-C or USB-A & C, plug and play	USB 2.0, USB-A, USB-C or USB-A & C, plug and play
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions (L × W × H)	175X218X109mm	175X218X109mm
	USB Cable Length	Control cable: 130 cm; Headset cable: 50 cm	Control cable: 130 cm; Headset cable: 50 cm
	Warranty	1 Year	1 Year
	Weight	185.5g	185.5g
	Certifications	CE , FCC	CE , FCC
	Operating Temperature	' -10°C +50°C	' -10°C +50°C

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, Renluoliu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App:+86 13392001358 <http://www.boxinltd.com>

	Headset Type	Headset Model: UC-006 USB Mono (Single-ear) Solution1	Headset Model: UC-006 Mono (Single-ear) Solution2
Audio	Microphone Type	1μm ECM array (1 omnidirectional)	1μm ECM array (1 unidirectional)
	Microphone Frequency Range	70Hz – 10kHz	70Hz – 8kHz
	Microphone Sensitivity	-40±3dB	-38±3dB
	Speaker Size	40mm	40mm
	Speaker Bandwidth	20Hz – 20kHz	20Hz – 20kHz
	Speaker Sensitivity	97±3dB	106±3dB
	Speaker Impedance	32Ω±15%	32Ω±15%
	ENC	Yes	/
	ANC	No	No
	Passive Noise Cancellation	Yes	No
Ease of Use	Call Control	Answer/End Call Microphone Mute (button or boom lift mechanism), Volume Up/Down	Answer/End Call Microphone Mute (button or boom lift mechanism), Volume Up/Down
	Microphone Boom Rotation Angle	270°	270°
	Busylight	No	No
	Ringtone	/	/
	Compatibility	Subject to actual product testing	Subject to actual product testing
Connectivity	Connection	USB 2.0, USB-A, USB-C or USB-A & C, plug and play	USB 2.0, USB-A, USB-C or USB-A & C, plug and play
	Box Contents	Headset, User Manual	Headset, User Manual
	Packaging Dimensions (L×W×H)	175X218X109mm	175X218X109mm
	USB Cable Length	Control cable: 130 cm; Headset cable: 50 cm	Control cable: 130 cm; Headset cable: 50 cm
	Warranty	1 Year	1 Year
	Weight	169.8g	169.8g
	Certifications	CE , FCC	CE , FCC
	Operating Temperature	-10°C to +50°C	-10°C to +50°C