

Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, RenluoLiu Road,
Tel: 86-86-752-3558855 Phone / WeChat / Whats App:+86 13392001358 <http://www.boxinltd.com>

	Headset Model	USB office headset BX-001
Audio	Microphone Type	1mic ECM array (1 omnidirectional)
	Microphone frequency range	70Hz – 10kHz
	Microphone sensitivity	-40±3dB
	Speaker size	30mm
	Speaker bandwidth	20Hz – 20kHz
	Speaker sensitivity	98±3dB
	Speaker impedance	32Ω±15%
	Environmental Noise Cancellation	Noise-canceling microphone
	Active Noise Cancellation	NO
	Passive Noise Cancellation	YES
Ease of use	Call control	Answer/End Call ,Microphone Mute (Button),Volume Up/Down
	Microphone Boom Rotation	270°
	Busylight	/
	Ringtone	/
	Compatibility	Windows PCs、 macOS Computers、 Laptops、 Desktop Computers、 USB-A Compatible Devices
Connectivity	Connection	USB 2.0 、 USB-A 、 Plug and play
	Box content	Headset, User Manual
	Packaging dimensions (L x W x H)	205x180X40mm
	USB cord length	Control cable: 120cm Headset cable: 60cm
	Warranty	1 Year
	Weight	Naked product: 126.5g ; Net weight: 222.5g (Includes paper box, paper tray, and instruction
	Certifications	CE,FCC,ROHS
	Operating temperature	-10°C to +50°C

	Headset Model	USB office headset BX-002
Audio	Microphone Type	1mic ECM array (1 omnidirectional)
	Microphone frequency range	100Hz – 10kHz
	Microphone sensitivity	-40±3dB
	Speaker size	30mm
	Speaker bandwidth	20Hz – 20kHz
	Speaker sensitivity	102±3dB
	Speaker impedance	32Ω±15%
	Environmental Noise	Noise-canceling microphone
	Active Noise Cancellation	No
	Passive Noise Cancellation	YES
Ease of use	Call control	Answer/End Call ,Microphone Mute (Button),Volume Up/Down
	Microphone Boom Rotation	180°
	Busylight	/
	Ringtone	/
	Compatibility	Windows PCs、 macOS Computers、 Laptops、 Desktop Computers、 USB-A Compatible Devices
Connectivity	Connection	USB 2.0 、 USB-A 、 Plug and play
	Box content	Headset , User Manual
	Packaging dimensions (L x W x	205x180X40mm
	USB cord length	Control cable: 120cm Headset cable: 60cm
	Warranty	1 Year
	Weight	Naked product: 126.5g ; Net weight: 222.5g (Includes paper box, paper tray, and instruction
	Certifications	CE,FCC,ROHS
	Operating temperature	-10°C to +50°C

	Headset Model	USB office headset BX-003
Audio	Microphone Type	1mic ECM array (1 omnidirectional)
	Microphone frequency range	50Hz – 10kHz
	Microphone sensitivity	-40±3dB
	Speaker size	40mm
	Speaker bandwidth	20Hz – 20kHz
	Speaker sensitivity	105±3dB
	Speaker impedance	32Ω±15%
	Environmental Noise	Noise-canceling microphone
	Active Noise Cancellation	NO
	Passive Noise Cancellation	YES
Ease of use	Call control	Answer/End Call ,Microphone Mute (Button),Volume Up/Down
	Microphone Boom Rotation	270°
	Busylight	/
	Ringtone	/
	Compatibility	Windows PCs、 macOS Computers、 Laptops、 Desktop Computers、 USB-A Compatible Devices
Connectivity	Connection	USB 2.0 、 USB-A 、 USB-C or USBA &C, Plug and play
	Box content	Headset, User Manual
	Packaging dimensions (L x W x	210x192X55mm
	USB cord length	Control cable: 120cm Headset cable: 60cm
	Warranty	1 Year
	Weight	Naked product: 187g ; Net weight: 322.5g (Includes paper box, paper tray, and instruction manual.)
	Certifications	CE,FCC,ROHS
	Operating temperature	-10°C to +50°C

	Headset Model	USB office headset BX-006
Audio	Microphone Type	1mic ECM array (1 omnidirectional)
	Microphone frequency range	50Hz – 10kHz
	Microphone sensitivity	-40±3dB
	Speaker size	40mm
	Speaker bandwidth	20Hz – 20kHz
	Speaker sensitivity	106±3dB
	Speaker impedance	32Ω±15%
	Environmental Noise	Noise-canceling microphone
	Active Noise Cancellation	No
	Passive Noise Cancellation	YES
Ease of use	Call control	Answer/End Call ,Microphone Mute (Button),Volume Up/Down
	Microphone Boom Rotation	270°
	Busylight	/
	Ringtone	/
	Compatibility	Windows PCs、 macOS Computers、 Laptops、 Desktop Computers、 USB-A Compatible Devices
Connectivity	Connection	USB 2.0 、 USB-A 、 USB-C or USBA &C, Plug and play
	Box content	Headset , User Manual
	Packaging dimensions (L x W x	210x192X55mm
	USB cord length	Control cable: 120cm Headset cable: 60cm
	Warranty	1 Year
	Weight	Naked product: 171.5g ; Net weight: 307g (Includes paper box, paper tray, and instruction manual.)
	Certifications	CE,FCC,ROHS
	Operating temperature	-10°C to +50°C

	Headset Model	USB office headset BX-200
Audio	Microphone Type	1mic ECM array (1 omnidirectional)
	Microphone frequency range	70Hz – 10kHz
	Microphone sensitivity	-38±3dB
	Speaker size	40mm
	Speaker bandwidth	20Hz – 20kHz
	Speaker sensitivity	105±3dB
	Speaker impedance	32Ω±15%
	Environmental Noise	Noise-canceling microphone
	Active Noise Cancellation	No
	Passive Noise Cancellation	YES
Ease of use	Call control	Answer/End Call ,Microphone Mute (Button),Volume Up/Down
	Microphone Boom Rotation	270°
	Busylight	/
	Ringtone	/
	Compatibility	Windows PCs、 macOS Computers、 Laptops、 Desktop Computers、 USB-A Compatible Devices
Connectivity	Connection	USB 2.0 、 USB-A, Plug and play
	Box content	Headset, User Manual
	Packaging dimensions (L x W x H)	210x192X55mm
	USB cord length	Control cable: 120cm Headset cable: 60cm
	Warranty	1 Year
	Weight	Naked product: 188g ; Net weight: 323.5g (Includes paper box, paper tray, and instruction manual.)
	Certifications	CE,FCC,ROHS
	Operating temperature	-10°C to +50°C

	Headset Model	USB office headset BX-392
Audio	Microphone Type	1mic ECM array (1 omnidirectional)
	Microphone frequency range	100Hz – 10kHz
	Microphone sensitivity	-37 ± 3dB
	Speaker size	40mm
	Speaker bandwidth	20Hz – 20kHz
	Speaker sensitivity	108±3dB
	Speaker impedance	32Ω±15%
	Environmental Noise	Noise-canceling microphone
	Active Noise Cancellation	NO
	Passive Noise Cancellation	YES
Ease of use	Call control	Answer/End Call ,Microphone Mute (Button),Volume Up/Down
	Microphone Boom Rotation	180°
	Busylight	/
	Ringtone	/
	Compatibility	Windows PCs、 macOS Computers、 Laptops、 Desktop Computers、 USB-A Compatible Devices
Connectivity	Connection	USB 2.0 、 USB-A, Plug and play
	Box content	Headset, User Manual
	Packaging dimensions (L x W x H)	210x192X55mm
	USB cord length	Control cable: 120cm Headset cable: 60cm
	Warranty	1 Year
	Weight	Naked product: 185g ; Net weight: 320.5g (Includes paper box, paper tray, and instruction manual.)
	Certifications	CE,FCC,ROHS
	Operating temperature	-10°C to +50°C